

GAMA DE CALDERAS SY-GB-HK

MODELO	DENOMINACIÓN	PRODUCCIÓN DE VAPOR NOMINAL	POTENCIA NOMINAL CON AGUA A 80°C	SUPERFICIE CALEFACCIÓN	VT	VS
HK-250	HK-250-9	2.500 kg/h	1.882 kW	60,7 m ²	7.170 litros	9 bar
	HK-250-11	2.500 kg/h	1.888 kW	60,7 m ²	7.170 litros	11 bar
	HK-250-13	2.500 kg/h	1.892 kW	60,7 m ²	7.170 litros	13 bar
	HK-250-15	2.500 kg/h	1.896 kW	60,7 m ²	7.170 litros	15 bar
	HK-250-17	2.500 kg/h	1.898 kW	60,7 m ²	7.170 litros	17 bar
HK-320	HK-320-9	3.200 kg/h	2.409 kW	64,8 m ²	7.700 litros	9 bar
	HK-320-11	3.200 kg/h	2.416 kW	64,8 m ²	7.700 litros	11 bar
	HK-320-13	3.200 kg/h	2.422 kW	64,8 m ²	7.700 litros	13 bar
	HK-320-15	3.200 kg/h	2.426 kW	64,8 m ²	7.700 litros	15 bar
	HK-320-17	3.200 kg/h	2.430 kW	64,8 m ²	7.700 litros	17 bar
HK-460	HK-460-9	4.600 kg/h	3.462 kW	84,0 m ²	9.500 litros	9 bar
	HK-460-11	4.600 kg/h	3.473 kW	84,0 m ²	9.500 litros	11 bar
	HK-460-13	4.600 kg/h	3.481 kW	84,0 m ²	9.500 litros	13 bar
	HK-460-15	4.600 kg/h	3.488 kW	84,0 m ²	9.500 litros	15 bar
	HK-460-17	4.600 kg/h	3.493 kW	84,0 m ²	9.500 litros	17 bar
HK-550	HK-550-9	5.500 kg/h	4.140 kW	106,0 m ²	9.210 litros	9 bar
	HK-550-11	5.500 kg/h	4.153 kW	106,0 m ²	9.210 litros	11 bar
	HK-550-13	5.500 kg/h	4.163 kW	106,0 m ²	9.210 litros	13 bar
	HK-550-15	5.500 kg/h	4.170 kW	106,0 m ²	9.210 litros	15 bar
	HK-550-17	5.500 kg/h	4.176 kW	106,0 m ²	9.210 litros	17 bar
HK-650	HK-650-9	6.500 kg/h	4.893 kW	128,0 m ²	10.200 litros	9 bar
	HK-650-11	6.500 kg/h	4.908 kW	128,0 m ²	10.200 litros	11 bar
	HK-650-13	6.500 kg/h	4.919 kW	128,0 m ²	10.200 litros	13 bar
	HK-650-15	6.500 kg/h	4.928 kW	128,0 m ²	10.200 litros	15 bar
	HK-650-17	6.500 kg/h	4.935 kW	128,0 m ²	10.200 litros	17 bar
HK-800	HK-800-9	8.000 kg/h	6.022 kW	155,0 m ²	14.600 litros	9 bar
	HK-800-11	8.000 kg/h	6.040 kW	155,0 m ²	14.600 litros	11 bar
	HK-800-13	8.000 kg/h	6.055 kW	155,0 m ²	14.600 litros	13 bar
	HK-800-15	8.000 kg/h	6.066 kW	155,0 m ²	14.600 litros	15 bar
	HK-800-17	8.000 kg/h	6.074 kW	155,0 m ²	14.600 litros	17 bar
HK-1000	HK-1000-9	10.000 kg/h	7.527 kW	198,0 m ²	16.900 litros	9 bar
	HK-1000-11	10.000 kg/h	7.551 kW	198,0 m ²	16.900 litros	11 bar
	HK-1000-13	10.000 kg/h	7.568 kW	198,0 m ²	16.900 litros	13 bar
	HK-1000-15	10.000 kg/h	7.582 kW	198,0 m ²	16.900 litros	15 bar
	HK-1000-17	10.000 kg/h	7.593 kW	198,0 m ²	16.900 litros	17 bar
HK-1200	HK-1200-9	12.000 kg/h	9.032 kW	207,0 m ²	20.300 litros	9 bar
	HK-1200-11	12.000 kg/h	9.061 kW	207,0 m ²	20.300 litros	11 bar
	HK-1200-13	12.000 kg/h	9.082 kW	207,0 m ²	20.300 litros	13 bar
	HK-1200-15	12.000 kg/h	9.099 kW	207,0 m ²	20.300 litros	15 bar
	HK-1200-17	12.000 kg/h	9.111 kW	207,0 m ²	20.300 litros	17 bar
HK-1400	HK-1400-9	14.000 kg/h	10.538 kW	282,0 m ²	27.800 litros	9 bar
	HK-1400-11	14.000 kg/h	10.571 kW	282,0 m ²	27.800 litros	11 bar
	HK-1400-13	14.000 kg/h	10.596 kW	282,0 m ²	27.800 litros	13 bar
	HK-1400-15	14.000 kg/h	10.615 kW	282,0 m ²	27.800 litros	15 bar
	HK-1400-17	14.000 kg/h	10.630 kW	282,0 m ²	27.800 litros	17 bar
HK-1600	HK-1600-9	16.000 kg/h	12.043 kW	315,3 m ²	29.420 litros	9 bar
	HK-1600-11	16.000 kg/h	12.081 kW	315,3 m ²	29.420 litros	11 bar
	HK-1600-13	16.000 kg/h	12.109 kW	315,3 m ²	29.420 litros	13 bar
	HK-1600-15	16.000 kg/h	12.131 kW	315,3 m ²	29.420 litros	15 bar
	HK-1600-17	16.000 kg/h	12.148 kW	315,3 m ²	29.420 litros	17 bar
HK-1800	HK-1800-9	18.000 kg/h	13.549 kW	473,0 m ²	33.570 litros	9 bar
	HK-1800-11	18.000 kg/h	13.591 kW	473,0 m ²	33.570 litros	11 bar
	HK-1800-13	18.000 kg/h	13.623 kW	473,0 m ²	33.570 litros	13 bar
	HK-1800-15	18.000 kg/h	13.648 kW	473,0 m ²	33.570 litros	15 bar
	HK-1800-17	18.000 kg/h	13.667 kW	473,0 m ²	33.570 litros	17 bar
HK-2000	HK-2000-9	20.000 kg/h	15.054 kW	480,3 m ²	46.550 litros	9 bar
	HK-2000-11	20.000 kg/h	15.101 kW	480,3 m ²	46.550 litros	11 bar
	HK-2000-13	20.000 kg/h	15.137 kW	480,3 m ²	46.550 litros	13 bar
	HK-2000-15	20.000 kg/h	15.164 kW	480,3 m ²	46.550 litros	15 bar
	HK-2000-17	20.000 kg/h	15.186 kW	480,3 m ²	46.550 litros	17 bar
HK-2500	HK-2500-9	25.000 kg/h	18.818 kW	674,9 m ²	49.570 litros	9 bar
	HK-2500-11	25.000 kg/h	18.876 kW	674,9 m ²	49.570 litros	11 bar
	HK-2500-13	25.000 kg/h	18.921 kW	674,9 m ²	49.570 litros	13 bar
	HK-2500-15	25.000 kg/h	18.955 kW	674,9 m ²	49.570 litros	15 bar
	HK-2500-17	25.000 kg/h	18.982 kW	674,9 m ²	49.570 litros	17 bar